

# ARMTEX® ATTACK™

Lightweight All-Polyester Double Jacket  
Rubber Lined Fire Hose

## COLORS:



### General Applications:

- Municipal fire departments
- Industrial fire brigades
- Shipboard fire fighting

### Construction:

Double-jacket polyester hose with a synthetic EPDM rubber ozone resistant lining.

**Abrasion Resistant Jacket** – Designed with superior abrasion resistance and kink resistance to resist damage from constant working conditions, even when using low pressure and straight bore nozzles. A smooth waterway surface for lower friction loss. Jacket color options include blue, green, black, orange, purple, red, tan, white and yellow.

### Service Temperature Range:

Remains flexible at temperatures as low as -40°F (-40°C).

### Features and Advantages:

- High Burst Rating – 1,200 psi up to 3" diameter.
- Superior Performance: Very low friction loss.
- ARMTEX® ATTACK™ is available in the sizes of 1 1/2", 1 3/4", 2", 2 1/2" and 3".
- Packs Tight – KFP's best packing and easiest to fold double-jacket, rubber-lined hose.
- Maintenance Free – Immune to mildew and rot.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- 10-year warranty.

### Packaging:

Available in 25', 50' and 100' lengths.

Distributed By

# Sterling

Hose, Reel & Supply, LLC.

855-577-HOSE

WWW.STERLINGHOSE.COM

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

## Lightweight All-Polyester Double Jacket Rubber Lined Fire Hose

### Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AA150BXXX-NH150	1 1/2	Blue	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150BXXX-NP150	1 1/2	Blue	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150GXXX-NH150	1 1/2	Green	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150GXXX-NP150	1 1/2	Green	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150LXXX-NH150	1 1/2	Black	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150LXXX-NP150	1 1/2	Black	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150OXXX-NH150	1 1/2	Orange	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150OXXX-NP150	1 1/2	Orange	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150PXXX-NH150	1 1/2	Purple	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150PXXX-NP150	1 1/2	Purple	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150RXXX-NH150	1 1/2	Red	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150RXXX-NP150	1 1/2	Red	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150TXXX-NH150	1 1/2	Tan	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150TXXX-NP150	1 1/2	Tan	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150WXXX-NH150	1 1/2	White	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150WXXX-NP150	1 1/2	White	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA150YXXX-NH150	1 1/2	Yellow	1 1/2	NST	1 15/16	400	800	1200	25/50/100	0.30
AA150YXXX-NP150	1 1/2	Yellow	1 1/2	NPSH	1 15/16	400	800	1200	25/50/100	0.30
AA175BXXX-NH150	1 3/4	Blue	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175BXXX-NP150	1 3/4	Blue	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175GXXX-NH150	1 3/4	Green	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175GXXX-NP150	1 3/4	Green	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175LXXX-NH150	1 3/4	Black	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175LXXX-NP150	1 3/4	Black	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175OXXX-NH150	1 3/4	Orange	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175OXXX-NP150	1 3/4	Orange	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175PXXX-NH150	1 3/4	Purple	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175PXXX-NP150	1 3/4	Purple	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175RXXX-NH150	1 3/4	Red	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175RXXX-NP150	1 3/4	Red	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175TXXX-NH150	1 3/4	Tan	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175TXXX-NP150	1 3/4	Tan	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

**Lightweight All-Polyester Double Jacket  
Rubber Lined Fire Hose**

**Nominal Specifications**

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AA175WXXX-NH150	1 3/4	White	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175WXXX-NP150	1 3/4	White	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/8	400	800	1200	25/50/100	0.34
AA175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/8	400	800	1200	25/50/100	0.34
AA200BXXX-NH150	2	Blue	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200BXXX-NP150	2	Blue	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200GXXX-NH150	2	Green	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200GXXX-NP150	2	Green	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200LXXX-NH150	2	Black	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200LXXX-NP150	2	Black	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200OXXX-NH150	2	Orange	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200OXXX-NP150	2	Orange	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200PXXX-NH150	2	Purple	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200PXXX-NP150	2	Purple	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200RXXX-NH150	2	Red	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200RXXX-NP150	2	Red	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200TXXX-NH150	2	Tan	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200TXXX-NP150	2	Tan	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200WXXX-NH150	2	White	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200WXXX-NP150	2	White	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA200YXXX-NH150	2	Yellow	1 1/2	NST	2 15/32	400	800	1200	25/50/100	0.44
AA200YXXX-NP150	2	Yellow	1 1/2	NPSH	2 15/32	400	800	1200	25/50/100	0.44
AA250BXXX-NH250	2 1/2	Blue	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250GXXX-NH250	2 1/2	Green	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250LXXX-NH250	2 1/2	Black	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250OXXX-NH250	2 1/2	Orange	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250PXXX-NH250	2 1/2	Purple	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250RXXX-NH250	2 1/2	Red	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250TXXX-NH250	2 1/2	Tan	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250WXXX-NH250	2 1/2	White	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	3	400	800	1200	25/50/100	0.50
AA300BXXX-NH250	3	Blue	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62

\*XXX = Available Lengths

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

## Lightweight All-Polyester Double Jacket Rubber Lined Fire Hose

### Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
AA300GXXX-NH250	3	Green	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300LXXX-NH250	3	Black	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300OXXX-NH250	3	Orange	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300PXXX-NH250	3	Purple	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300RXXX-NH250	3	Red	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300TXXX-NH250	3	Tan	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300WXXX-NH250	3	White	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62
AA300YXXX-NH250	3	Yellow	2 1/2	NST	3 1/2	400	800	1200	25/50/100	0.62

\*XXX = Available Lengths

Distributed By

# Sterling

Hose, Reel & Supply, LLC.

855-577-HOSE

WWW.STERLINGHOSE.COM

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.