

JAFx4™

Distributed By
Sterling

Hose, Reel & Supply, LLC.

855-577-HOSE

WWW.STERLINGHOSE.COM

The World's TOUGHEST Fire Hose

COLOR:



General Applications:

- Active municipal departments
- Heavy industrial municipalities
- Refining, chemical and utility industries
- Coarse, abrasive landscapes
- Marine environments
- Daily use applications such as wash down and sewage treatment plants

Construction:

Revolutionary co-extrusion technology creates a “Four Layer Hose-In-One Operation” without the use of glues or adhesives thereby forming a homogeneous hose which cannot delaminate.

Service Temperature Range:

-4°F (-20°C) to +176°F (+80°C)

Features and Advantages:

- Resists burn-through.
- Super resistant to abrasion.
- Underwriters Laboratories (UL) 19 and Underwriters Laboratories of Canada (ULC) – S511-14 Certified* – 1 1/2", 1 3/4", 2", 2 1/2 .
- Excellent resistance to heat, ozone, weather, most chemicals (acids, bases, salts, oils, solvents, etc.), flame, wear, tear and puncture.
- Highly flexible and smooth inner lining provides excellent dilation characteristics with low friction loss and high kinking resistance.
- Meets or exceeds National Fire Protection Association (NFPA) 1961 Standard on Fire Hose (current edition).
- ISO 9001 - JAFx4 fire hose products are manufactured in a registered facility in Barcelona, Spain.
- 10-year warranty.

Packaging:

Available in 25', 50' and 100' lengths.



BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.

Bulk Hose Lengths

Nominal Specifications

Part Number*	Size (in)	Color	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
56H1FX4-XX	1	Yellow	1 3/16	580	1160	1740	25/50/100	0.160
56H15FX4-XX	1 1/2	Yellow	1 3/4	300	600	900	25/50/100	0.296
56H175FX4-XX	1 3/4	Yellow	2 1/16	300	600	900	25/50/100	0.343
56H2FX4-XX	2	Yellow	2 9/32	300	600	900	25/50/100	0.390
56H25FX4-XX	2 1/2	Yellow	2 13/16	300	600	900	25/50/100	0.517
56H4FX4-XX	4	Yellow	4 9/32	250	500	750	25/50/100	0.874
56H5FX4-XX	5	Yellow	5 3/8	250	500	750	25/50/100	1.109

*XXX = Available Lengths

Assembled Lengths

Nominal Specifications

Part Number*	Size (in)	Color	Coupling Size (in)	Coupling Type	Bowl Size (in)	Service Test (psi)	Proof Test (psi)	Burst Test (psi)	Available Lengths (ft)	Weight Uncoupled (lbs/ft)
JX100YXXX-NH100	1	Yellow	1	NST	1 3/16	580	1160	1740	25/50/100	0.160
JX100YXXX-NP100	1	Yellow	1	NPSH	1 3/4	580	1160	1740	25/50/100	0.160
JX150YXXX-NH150	1 1/2	Yellow	1 1/2	NST	1 3/4	300	600	900	25/50/100	0.296
JX150YXXX-NP150	1 1/2	Yellow	1 1/2	NPSH	1 3/4	300	600	900	25/50/100	0.296
JX175YXXX-NH150	1 3/4	Yellow	1 1/2	NST	2 1/16	300	600	900	25/50/100	0.343
JX175YXXX-NP150	1 3/4	Yellow	1 1/2	NPSH	2 1/16	300	600	900	25/50/100	0.343
JX200YXXX-NH150	2	Yellow	1 1/2	NST	2 9/32	300	600	900	25/50/100	0.390
JX200YXXX-NP150	2	Yellow	1 1/2	NPSH	2 9/32	300	600	900	25/50/100	0.390
JX250YXXX-NH250	2 1/2	Yellow	2 1/2	NST	2 13/16	300	600	900	25/50/100	0.517
JX400YXXX-SZ400	4	Yellow	4	Storz	4 9/32	250	500	750	25/50/100	0.874
JX500YXXX-SZ500	5	Yellow	5	Storz	5 3/8	225	450	675	25/50/100	1.109

*XXX = Available Lengths

Distributed By

Sterling

Hose, Reel & Supply, LLC.

855-577-HOSE

WWW.STERLINGHOSE.COM

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.