

Oilvey™ 20

PU Layflat Hoses

Designed for transferring oil or fuel temporarily etc. ...



Oilvey 20 is one type of through-the-weave polyurethane (PU) covered hose. Oilvey 20 hoses shall be made from 100% high tenacity synthetic yarn circular woven and completely, totally embedded in the PU compound, excellent protected against mechanical damage, forming a single homogenous construction without the use of any glues or adhesives of any type. Incorporated copper wire is used to transfer static electricity.

Application: Suitable for use and recommended for temporarily transferring oil, fuel, and produced water transfer etc.

Inner tube and cover: Smooth PU cover and tube.

Reinforcement: Circular woven polyester jacket with static wire incorporated.

Operating Temperature Range: From -60° F to 176°F (-50° C to 80° C)

Standard Color: NATO Green, other colors available per request

Standard Length: 50ft, 100ft, 330ft/100m, 660ft/200m; other lengths available per request;

Couplings: Steel HPHC FM couplings, etc.

Warranty: Ten years guarantee

Recommended for :

Temporarily oil or fuel transfer solutions
Produced Water Transfer Solutions
Other

Oilvey™ 20

ID		Wall Thickness		Weight		Working Pressure	Bursting Pressure
Inch	mm	Inch	mm	lbs/ft	kg/m	PSI/bar	PSI/bar
4"	103+2.0	0.20"	5.2	1.29	1.93	400PSI/28bar	1200PSI/84bar
6"	153+2.5	0.23"	5.9	2.26	3.37	400PSI/28bar	1200PSI/84bar
8"	204+3.0	0.24"	6.2	3.5	5.21	365PSI/25bar	1100PSI/75bar